



MOBILE REFRIGERATION BY DOMETIC

EXPERTISE YOU CAN BUILD ON

Whether car or truck, motorhome or yacht, refrigerated van or special vehicle – mobile refrigeration by Dometic is leading the way in the market. Four decades of development work have given rise to a product range that brings out the best of all refrigeration technologies.

Powerful compressor cooling, lightweight and low-cost thermoelectrics, noiseless absorption technology with three energy sources – the Dometic range gives you a multitude of options. So, whenever it comes to creating high-performance cooling solutions in confined spaces – build on the expertise of the market leader! Take your pick from a range that has convinced consumers, stockists, vehicle outfitters and automotive manufacturers worldwide.



COMPRESSOR COOLERS

Compressor coolers provide excellent cooling performance, even at extreme ambient temperatures and with minimal power consumption. They can be used for standard refrigeration as well as for deep-freezing.

PAGE 82 – 94



THERMOELECTRIC COOLERS

Thermoelectric coolers provide active cooling up to 27 °C below the ambient temperature (depending on the model). They can be used for refrigeration as well as for keeping food warm. They are lightweight and easy to transport.

PAGE 95 – 101



ABSORPTION COOLERS

Noiseless cooling with three energy sources for maximum flexibility and independence. Absorption coolers can be run on 12 volts, 230 volts, or gas when electricity is unavailable.

PAGE 102 – 103



PASSIVE COOLERS

Well insulated and packed with ice cubes or ice packs, our passive coolers keep the contents fresh for up to several days in all weather conditions, and without requiring any external power supply.




PAGE 104 – 107



DOMETIC COOLFREEZE CFX 28

4.30

Portable compressor cooler and freezer, 26 l

  	Storage volume	approx. 26 l
	Connections	12 / 24 V DC, 100–240 V AC
	Temperature range	+10 °C to –22 °C
	Power input	40 W
	Current consumption at 12 V	0.30 Ah/h at +20 °C ambient temperature, at +5 °C interior temperature
	Energy class	A++
	Insulation	PU foam all around
	System	Fully hermetic compressor with integrated control electronics, low-voltage protection / electronic fuse, automatic reverse pole protection, electronic thermostat
	Refrigerant	R134a: 38 g, CO ₂ equivalent: 0.054 t, Global warming potential (GWP): 1430
	Quality Features	Deep freezing down to –22 °C, excellent cooling performance even at extremely high outside temperatures, CFX special electronics with digital temperature display, extremely efficient and superbly quiet operation, USB connection, drain plugs make cleaning simple, suitable for solar operation, heavy-duty version
	Material	Cabinet: PP + ABS, Lid: PE
	Colour	Pale grey / dark grey
	Weight	13.1
Test marks	TÜV/GS, E-certified (Automotive EMC Directive)	
Scope of delivery	Removable wire basket, Detachable carrying handles	
Product	Ref. No.	Ref. No. UK
Dometic CoolFreeze CFX 28	9600000468	9600000469
/ Optional extras see p.87		

DOMETIC CFX3 COMPRESSOR COOLERS

THE POWER TO BE PRESENT



Take control of outdoor adventures like never before with the Dometic CFX3. Enjoy reliably fresh food and cold drinks thanks to Dometic's market leading VM303 variable-speed compressor cooling technology. Its optimised software ensures superior cooling, freezing and energy efficiency. The CFX3 features durable and

lightweight fender frames to protect the cooler, making it ideal for use in harsh outdoor environments. Strong, spring-loaded aluminum handles make it easy to lift and carry. Adjust the cooling temperature of your CFX3 on the TFT display screen or download the Dometic app and roam free without worry.

DOMETIC CFX3 35

4.30


Portable compressor cooler and freezer, 32 l


 	Storage volume	approx. 32 l
	Connections	12 / 24 V DC, 100–240 V AC
	Temperature range	+10 °C to –22 °C
	Power input	50 W
	Current consumption at 12 V	0.47 Ah/h at +20 °C ambient temperature at +4 °C interior temperature
	Energy class	A++
	Insulation	PU foam all around
	System	Fully hermetic compressor with integrated control electronics, low-voltage protection / electronic fuse, automatic reverse pole protection, electronic thermostat
	Refrigerant	R134a: 38 g, CO ₂ equivalent: 0.054 t, Global warming potential (GWP): 1430
	Quality Features	<ul style="list-style-type: none"> Heavy-duty yet lightweight ExoFrame construction with fender frame protected edges and aluminum alloy handles Powerful VM303 compressor cooling technology efficiently refrigerates and deep-freezes to –22 °C Easy-to-read High-Resolution Color Display and soft touch buttons enabling seamless control and monitoring of cooler performance CFX3 App allows temperature control via WiFi or Bluetooth and provides performance history 3-stage dynamic battery protection system prevents dead car battery or allows deep draw on dual batteries Active Gasket Technology provides a superior seal to retain cool air and minimize power consumption
	Material	Cabinet: PP + ABS, Lid: PE
	Colour	Pale grey / dark grey
	Weight	16.9 kg
Test marks	TÜV/GS, E-certified (Automotive EMC Directive)	
Scope of delivery	1 cooler, 1 manual, 1 connection cable for 12/24 V connection, 1 connection cable for 100 - 240 V connection, removable wire baskets	
Product	Ref. No.	Ref. No. UK
Dometic CFX3 35	9600025324	9600025325
/ Optional extras see p.87		

DOMETIC CFX3 45

4.30


Portable compressor cooler and freezer, 40 l


	Storage volume	approx. 40 l	
	Connections	12 / 24 V DC, 100–240 V AC	
	Temperature range	+10 °C to –22 °C	
	Power input	52 W	
	Current consumption at 12 V	0.49 Ah/h at +20 °C ambient temperature, at +4 °C interior temperature	
	Energy class	A++	
	Insulation	PU foam all around	
	System	Fully hermetic compressor with integrated control electronics, low-voltage protection / electronic fuse, automatic reverse pole protection, electronic thermostat	
	Refrigerant	R134a: 42 g, CO ₂ equivalent: 0.060 t, Global warming potential (GWP): 1430	
	Quality Features	<ul style="list-style-type: none"> • See CFX3 35, page 83 	
Material	Cabinet: PP + ABS, Lid: PE		
Colour	Pale grey / dark grey		
Weight	18.7 kg		
Test marks	TÜV/GS, E-certified (Automotive EMC Directive)		
Scope of delivery	1 cooler, 1 manual, 1 connection cable for 12/24 V connection, 1 connection cable for 100 - 240 V connection, removable wire baskets		
Product	Ref. No.	Ref. No. UK	
Dometic CFX3 45	9600025326	9600025327	
/ Optional extras see p.87			

**DOMETIC CFX3 55IM**

4.30


Portable compressor cooler and freezer, 46 l


	Storage volume	approx. 46 l	
	Connections	12 / 24 V DC, 100–240 V AC	
	Temperature range	+10 °C to –22 °C	
	Power input	52 W	
	Current consumption at 12 V	0.59 Ah/h at +20 °C ambient temperature both at +4 °C interior temperature	
	Energy class	A++	
	Insulation	PU foam all around	
	System	Fully hermetic compressor with integrated control electronics, low-voltage protection / electronic fuse, automatic reverse pole protection, electronic thermostat	
	Refrigerant	R134a: 45 g, CO ₂ equivalent: 0.064 t, Global warming potential (GWP): 1430	
	Quality Features	<ul style="list-style-type: none"> • See CFX3 35, page 83 • Built-in ice maker produces ice in a matter of hours 	
Material	Cabinet: PP + ABS, Lid: PE		
Colour	Pale grey / dark grey		
Weight	21.3 kg		
Test marks	TÜV/GS, E-certified (Automotive EMC Directive)		
Scope of delivery	1 cooler, 1 manual, 1 connection cable for 12/24 V connection, 1 connection cable for 100 - 240 V connection, removable wire baskets, 1 icemaker		
Product	Ref. No.	Ref. No. UK	
Dometic CFX3 55IM	9600025330	9600025331	
/ Optional extras see p.87			

**DOMETIC CFX3 55**

4.30


Portable compressor cooler and freezer, 48 l


	Storage volume	approx. 48 l	
	Connections	12 / 24 V DC, 100–240 V AC	
	Temperature range	+10 °C to –22 °C	
	Power input	50 W	
	Current consumption at 12 V	0.56 Ah/h at +20 °C ambient temperature, at +4 °C interior temperature	
	Energy class	A++	
	Insulation	PU foam all around	
	System	Fully hermetic compressor with integrated control electronics, low-voltage protection / electronic fuse, automatic reverse pole protection, electronic thermostat	
	Refrigerant	R134a: 45 g, CO ₂ equivalent: 0.064 t, Global warming potential (GWP): 1430	
	Quality Features	<ul style="list-style-type: none"> • See CFX3 35, page 83 	
Material	Cabinet: PP + ABS, Lid: PE		
Colour	Pale grey / dark grey		
Weight	20.4 kg		
Test marks	TÜV/GS, E-certified (Automotive EMC Directive)		
Scope of delivery	1 cooler, 1 manual, 1 connection cable for 12/24 V connection, 1 connection cable for 100 - 240 V connection, removable wire baskets		
Product	Ref. No.	Ref. No. UK	
Dometic CFX3 55	9600025328	9600025329	
/ Optional extras see p.87			

**DOMETIC CFX3 100**

4.30

Mobile compressor cooler and freezer, 88 l



	Storage volume	approx. 88 l	
	Connections	12 / 24 V DC, 100–240 V AC	
	Temperature range	+10 °C to –22 °C	
	Power input	73 W	
	Current consumption at 12 V	0.91 Ah/h at +20 °C ambient temperature, at +4 °C interior temperature	
	Energy class	A+	
	Insulation	PU foam all around	
	System	Fully hermetic compressor with integrated control electronics, low-voltage protection / electronic fuse, automatic reverse pole protection, electronic thermostat	
	Refrigerant	R134a: 60 g, CO ₂ equivalent: 0.086 t, Global warming potential (GWP): 1430	
	Quality Features	<ul style="list-style-type: none"> • See CFX3 35, page 83 	
Material	Cabinet: PP + ABS, Lid: PE		
Colour	Pale grey / dark grey		
Weight	29.6 kg		
Test marks	TÜV/GS, E-certified (Automotive EMC Directive)		
Scope of delivery	1 cooler, 1 manual, 1 connection cable for 12/24 V connection, 1 connection cable for 100 - 240 V connection, removable wire baskets		
Product	Ref. No.	Ref. No. UK	
Dometic CFX3 100	9600025336	9600025337	
/ Optional extras see p.87			



DOMETIC CFX3 75DZ

Mobile compressor dual-zone cooler and freezer, 65 l

4.30





Storage volume	approx. 65 l (39 l / 26 l)
Connections	12 / 24 V DC, 100–240 V AC
Temperature range	+10 °C to –22 °C
Power input	59 W
Current consumption at 12 V	0.68 Ah/h at +20 °C ambient temperature, at +4 °C interior temperature
Energy class	A+
Insulation	PU foam all around
System	Fully hermetic compressor with integrated control electronics, low-voltage protection / electronic fuse, automatic reverse pole protection, electronic thermostat
Refrigerant	R134a: 59 g, CO ₂ equivalent: 0.084 t, Global warming potential (GWP): 1430
Quality Features	<ul style="list-style-type: none"> See CFX3 35, page 83 Dual storage compartments allow independently variable temperature control for simultaneous cooling and freezing
Material	Cabinet: PP + ABS, Lid: PE
Colour	Pale grey / dark grey
Weight	27.8 kg
Test marks	TÜV/GS, E-certified (Automotive EMC Directive)
Scope of delivery	1 cooler, 1 manual, 1 connection cable for 12/24 V connection, 1 connection cable for 100 - 240 V connection, removable wire baskets
Product	Ref. No. Ref. No. UK
Dometic CFX3 75DZ	9600025332 9600025333
/ Optional extras see p.87	

DOMETIC CFX3 95DZ

Mobile compressor dual-zone cooler and freezer, 82 l

4.30



Storage volume	approx. 82 l (48 l / 34 l)
Connections	12 / 24 V DC, 100–240 V AC
Temperature range	+10 °C to –22 °C
Power input	61 W
Current consumption at 12 V	0.80 Ah/h at +20 °C ambient temperature, at +4 °C interior temperature
Energy class	A+
Insulation	PU foam all around
System	Fully hermetic compressor with integrated control electronics, low-voltage protection / electronic fuse, automatic reverse pole protection, electronic thermostat
Refrigerant	R134a: 67 g, CO ₂ equivalent: 0.096 t, Global warming potential (GWP): 1430
Quality Features	<ul style="list-style-type: none"> See CFX3 35, page 83 Dual storage compartments allow independently variable temperature control for simultaneous cooling and freezing
Material	Cabinet: PP + ABS, Lid: PE
Colour	Pale grey / dark grey
Weight	29.8 kg
Test marks	TÜV/GS, E-certified (Automotive EMC Directive)
Scope of delivery	1 cooler, 1 manual, 1 connection cable for 12/24 V connection, 1 connection cable for 100 - 240 V connection, removable wire baskets
Product	Ref. No. Ref. No. UK
Dometic CFX3 95DZ	9600025334 9600025335
/ Optional extras see p.87	

BATTERY PACKS FOR CFX3, CDF, CF COOLING BOXES

Portable lithium batteries

	PLB40	BP124
Battery capacity	40 Ah / 512 Wh	10 Ah / 250 Wh
Chemistry	Lithium Iron Phosphate (LiFePO4)	Li-NMC
Battery voltage	12.8 V DC	25,2 V DC (19,25 V – 29,4 V DC)
DC output	15 A	20 A
Continuous output	150 W (per 12 V connection)	385 W
Dimensions (W x H x D)	197 x 257 x 197 mm	150 x 65 x 150 mm
Weight	7.54 kg	3.1 kg
Quality Features	Three-way charging via 12 V socket, solar panel or AC house power, Extremely lightweight, ergonomically designed stainless steel carry-handle, Built-in LCD screen, Suitable for the CFX3, CDF, CF series, Powerful battery cells provide 512 Wh of energy, 40 Ah	High-quality lithium-ion cells (Samsung ICR18650-26F), integrated charger, Supplying energy to 24-volt compressor coolers, Suitable for the CFX3, CDF, CF series
Scope of delivery	40Ah Lithium ion Phosphate battery pack, 10Amp ACDC charger, DC cable extension with Cig plug & Anderson connector, Colour gift box packaging	Battery pack, charger, charging cable
Test marks	IP class IP44	e-certified (Automotive EMC Directive)
Product	Ref. No.	
Dometic BP124, batterypack	9600005902	
Dometic PLB40, portable lithium battery, 40 Ah	9600012878	

**DOMETIC COOLFREEZE CF-CBS**

Coolbox stand

- No need to strain your back – place your coolbox at a comfortable height
- The sturdiest stand within its category: load capacity up to 80 kg
- With a light weight of 2 kg and full collapsibility, transport is easy!

Ref. No. 9600000689

**DOMETIC CI-FK**

Fastening straps for coolboxes

- Heavy duty straps
- Low profile tie-down anchor points

Ref. No. 9108400905



DOMETIC CFF COMPRESSOR COOLERS

INNOVATIVE REVERSIBLE OPENING LID



The CFF series provides the essentials; serious spacious storage combined with impeccable insulation, topped off with an attractive modern design. This new release is bound to have outdoor enthusiasts excited everywhere because now, everyone can enjoy everything cool that Dometic has to offer. Dometic has designed the CFF series so that it contains the most efficient interior storage

layout, along with a double sided opening lid; allowing access from either side. Adventurers will love the new glass filled nylon and steel handles, making for a comfortable and reliable use first time, every time.

DOMETIC CFF 35

4.30



Portable compressor cooler and freezer, 30 l

 	Storage volume	approx. 30 l
	Connections	12 / 24 V DC, 100–240 V AC
	Temperature range	+10 °C to –18 °C
	Power input	53 W
	Current consumption at 12 V	0.57 Ah/h at +20 °C ambient temperature, at +4 °C interior temperature
	Energy class	A+
	Insulation	PU foam all around
	System	Fully hermetic compressor with integrated control electronics, low-voltage protection / electronic fuse, automatic reverse pole protection, electronic thermostat
	Refrigerant	R134a: 40 g, CO ₂ equivalent: 0.057 t, Global warming potential (GWP): 1430
	Quality Features	<ul style="list-style-type: none"> • Single compartment allows either refrigeration or freezing • Energy efficient design provides fast and excellent cooling and freezing, even in extremely high outside temperatures • Double sided opening lid • Compact design ensures excellent portability
	Material	Cabinet: PP + ABS, Lid: PE
Colour	Pale grey / dark grey	
Weight	17.2 kg	
Test marks	TÜV/GS, E-certified (Automotive EMC Directive)	
Scope of delivery	1 cooler, 1 connection cable for 12/24 V DC connection, 1 connection cable for 100 - 240V AC connection, 2 carrying handles, 1 removable wire basket, 1 manual	
Product	Ref. No.	Ref. No. UK
Dometic CFF 35	9600024842	9600026458

DOMETIC CFF 45

4.30




Portable compressor cooler and freezer, 38 l

 	Storage volume	approx. 38 l
	Connections	12 / 24 V DC, 100–240 V AC
	Temperature range	+10 °C to –18 °C
	Power input	53 W
	Current consumption at 12 V	0.60 Ah/h at +20 °C ambient temperature, at +4 °C interior temperature
	Energy class	A+
	Insulation	PU foam all around
	System	Fully hermetic compressor with integrated control electronics, low-voltage protection / electronic fuse, automatic reverse pole protection, electronic thermostat
	Refrigerant	R134a: 50 g, CO ₂ equivalent: 0.072 t, Global warming potential (GWP): 1430
	Quality Features	<ul style="list-style-type: none"> • Single compartment allows either refrigeration or freezing • Energy efficient design provides fast and excellent cooling and freezing, even in extremely high outside temperatures • Double sided opening lid • Compact design ensures excellent portability
	Material	Cabinet: PP + ABS, Lid: PE
Colour	Pale grey / dark grey	
Weight	18.6 kg	
Test marks	TÜV/GS, E-certified (Automotive EMC Directive)	
Scope of delivery	1 cooler, 1 connection cable for 12/24 V DC connection, 1 connection cable for 100 - 240V AC connection, 2 carrying handles, 1 removable wire basket, 1 manual	
Product	Ref. No.	Ref. No. UK
Dometic CFF 45	9600012977	9600026459

DOMETIC COOLFREEZE CF 11

4.30



Portable compressor cooler and freezer, 10.5 l

  	Storage volume	approx. 10.5 l		
	Connections	12 / 24 V DC, 100–240 V AC		
	Temperature range	+10 °C to –18 °C		
	Power input	35 W		
	Current consumption at 12 V	0.29 Ah/h at +20 °C ambient temperature, at +5 °C interior temperature		
	Energy class	A++		
	Insulation	PU foam all around		
	System	Fully hermetic compressor with integrated control electronics, low-voltage protection / electronic fuse, automatic reverse pole protection, electronic thermostat		
	Refrigerant	R134a: 28 g, CO ₂ equivalent: 0.040 t, Global warming potential (GWP): 1430		
	Quality Features	3-stage battery protection, LED interior light, Electronic thermostat with digital temperature display, adjustable shoulder strap, two drink holders, easy and secure fastening with the vehicle safety belt		
Material	Cabinet: PP, Lid: PE			
Colour	Pale grey / dark grey			
Weight	8.5 kg			
Test marks	E-certified (Automotive EMC Directive)			
Product		Ref. No.	Ref. No. UK	
Dometic CoolFreeze CF 11		9600005337	9600005338	
/ Optional extras see p. 93				

DOMETIC COOLFREEZE CF 26

4.30




Portable compressor cooler and freezer, 21.5 l

 	Storage volume	approx. 21.5 l, 4 l for fresh food		
	Connections	12 / 24 V DC, 100–240 V AC		
	Temperature range	+10 °C to –18 °C		
	Power input	35 W		
	Current consumption at 12 V	0.29 Ah/h at +20 °C ambient temperature, at +5 °C interior temperature		
	Energy class	A++		
	Insulation	PU foam all around		
	System	Fully hermetic compressor with integrated control electronics, low-voltage protection / electronic fuse, automatic reverse pole protection, electronic thermostat		
	Refrigerant	R134a: 28 g, CO ₂ equivalent: 0.040 t, Global warming potential (GWP): 1430		
	Quality Features	3-stage battery protection, LED interior light, Electronic thermostat with digital temperature display, adjustable shoulder strap, two drink holders, easy and secure fastening with the vehicle safety belt		
Material	Cabinet: PP, Lid: PE			
Colour	Pale grey / dark grey			
Weight	10.5 kg			
Test marks	E-certified (Automotive EMC Directive)			
Product		Ref. No.	Ref. No. UK	
Dometic CoolFreeze CF 26		9600005341	9600005343	
/ Optional extras see p. 93				

DOMETIC COOLFREEZE CF 16

4.30



Portable compressor cooler and freezer, 15 l

  	Storage volume	approx. 15 l		
	Connections	12 / 24 V DC, 100–240 V AC		
	Temperature range	+10 °C to –18 °C		
	Power input	35 W		
	Current consumption at 12 V	0.21 Ah/h at +20 °C ambient temperature, at +5 °C interior temperature		
	Energy class	A++		
	Insulation	PU foam all around		
	System	Fully hermetic compressor with integrated control electronics, low-voltage protection / electronic fuse, automatic reverse pole protection, electronic thermostat		
	Refrigerant	R134a: 30 g, CO ₂ equivalent: 0.043 t, Global warming potential (GWP): 1430		
	Quality Features	3-stage battery protection, LED interior light, CF special electronics with digital temperature display, soft-start and turbo cooler function, extremely slim design, vertical space for two 1 litre bottles, detachable lid		
Material	Cabinet: PP, Lid: PE			
Colour	Pale grey / dark grey			
Weight	9.5 kg			
Test marks	TÜV/GS, E-certified (Automotive EMC Directive)			
Product		Ref. No.	Ref. No. UK	
Dometic CoolFreeze CF 16		9600005339	9600005340	
/ Optional extras see p. 93				

DOMETIC COOLFREEZE CDF 18

4.21


Portable compressor cooler and freezer, 18 l

 	Storage volume	approx. 18 l		
	Connections	12 / 24 V DC		
	Temperature range	+10 °C to –18 °C		
	Power input	35 W		
	Current consumption at 12 V	0.38 Ah/h at +20 °C ambient temperature, at +5 °C interior temperature		
	Insulation	PU foam all around		
	System	Fully hermetic compressor with integrated control electronics, low voltage protection / electronic fuse, automatic reverse pole protection, electronic thermostat		
	Refrigerant	R134a: 32 g, CO ₂ equivalent: 0,046 t, Global warming potential (GWP): 1430		
	Quality Features	Detachable lid (lid mount at the side), vertical space for standing 1.5-litre bottles		
	Material	Cabinet: PP, Lid: PE		
Colour	Pale grey / dark grey			
Weight	11.5 kg			
Test marks	TÜV/GS, E-certified (Automotive EMC Directive)			
Product		Ref. No.		
Dometic CoolFreeze CDF 18		9600000460		
/ Optional extras see p. 93				

DOMETIC COOLFREEZE CDF 36

4.21


Portable compressor cooler and freezer, 31 l

	Storage volume	approx. 31 l
	Connections	12 / 24 V DC
	Temperature range	+10 °C to -15 °C
	Power input	45 W
	Current consumption at 12 V	0.75 Ah/h at +20 °C ambient temperature, at +5 °C interior temperature
	Insulation	PU foam all around
	System	Fully hermetic compressor with integrated control electronics, low voltage protection / electronic fuse, automatic reverse pole protection, electronic thermostat
	Refrigerant	R134a: 38 g, CO ₂ equivalent: 0.054 t, Global warming potential (GWP): 1430
	Quality Features	Detachable lid (lid mount at the front), vertical space for standing 1.5-litre bottles
	Material	Cabinet: PP, Lid: PE
Colour	Pale grey / dark grey	
Weight	17 kg	
Test marks	TÜV/GS, E-certified (Automotive EMC Directive)	
Product		Ref. No.
Dometic CoolFreeze CDF 36		9600005344
/ Optional extras see p. 93		

DOMETIC COOLFREEZE CDF 46


4.21

Portable compressor cooler and freezer, 39 l

	Storage volume	approx. 39 l
	Connections	12 / 24 V DC
	Temperature range	+10 °C to -15 °C
	Power input	45W
	Current consumption at 12 V	0.94 Ah/h at +20 °C ambient temperature, at +5 °C interior temperature
	Insulation	PU foam all around
	System	Fully hermetic compressor with integrated control electronics, low voltage protection / electronic fuse, automatic reverse pole protection, electronic thermostat
	Refrigerant	R134a: 42 g, CO ₂ equivalent: 0.060 t, Global warming potential (GWP): 1430
	Quality Features	Detachable lid (lid mount at the front), vertical space for standing 2-litre bottles
	Material	Cabinet: PP, Lid: PE
Colour	Pale grey / dark grey	
Weight	20 kg	
Test marks	TÜV/GS, E-certified (Automotive EMC Directive)	
Product		Ref. No.
Dometic CoolFreeze CDF 46		9600000462
/ Optional extras see p. 93		

BATTERY PACKS FOR CFX3, CDF, CF COOLING BOXES

Portable lithium batteries

	PLB40	BP124	
	Battery capacity	40 Ah / 512 Wh	10 Ah / 250 Wh
	Chemistry	Lithium Iron Phosphate (LiFePO4)	Li-NMC
	Battery voltage	12.8 V DC	25,2 V DC (19,25 V – 29,4 V)
	DC output	15 A	20 A
	Continuous output	150 W (per 12 V connection)	385 W
	Dimensions (W x H x D)	197 x 257 x 197 mm	150 x 65 x 150 mm
	Weight	7.54 kg	3.1 kg
	Quality Features	Three-way charging via 12 V socket, solar panel or AC house power, Extremely lightweight, ergonomically designed stainless steel carry-handle, Built-in LCD screen, Suitable for the CFX3, CDF, CF series, Powerful battery cells provide 512 Wh of energy, 40 Ah	High-quality lithium-ion cells (Samsung ICR18650-26F), integrated charger, Supplying energy to 24-volt compressor coolers, Suitable for the CFX3, CDF, CF series
	Scope of delivery	40Ah Lithium ion Phosphate battery pack, 10Amp ACDC charger, DC cable extension with Cig plug & Anderson connector, Colour gift box packaging	Battery pack, charger, charging cable
	Test marks	IP class IP44	e-certified (Automotive EMC Directive)
Product		Ref. No.	
Dometic BP124, batterypack		9600005902	
Dometic PLB40, portable lithium battery, 40 Ah		9600012878	

**DOMETIC COOLPOWER EPS 100**

Mains adapter, connects 24 V appliances to 230 V mains

- Connects 24 V DC cooling boxes to the mains power socket
- Works well anywhere in the world
- Suitable for fixed installation
- With mains priority circuit for 12 or 24 V batteries

Ref. No. 9600000440

**DOMETIC COOLPOWER MPS 35**

Mains adapter, connects 24 V appliances to 110–240 V mains, 110 W

- Connects 24 V DC cooling boxes to the mains power socket
- Works well anywhere in the world
- Suitable for fixed installation
- With mains priority circuit for 12 or 24 V batteries

Ref. No. 9600000445

**DOMETIC COOLFREEZE CF-CDF-FK**

Vehicle fixing kit for CF 16 – 50, CDF 16 – 46



- For secure use of cooler while on the move
- For safe fastening of cooler
- Universal fixing kit to suit CoolFreeze CF 16 to CF 50, CDF 16 to CDF 46


Ref. No. 9105303708

DOMETIC CK 40D HYBRID

Portable hybrid cooler and freezer, 38 l

4.21

 	Storage volume	approx. 38 l				
	Connections	12 V DC (thermoelectrics) 230 V AC (compressor)				
	Temperature range	DC: cooling up to 20 °C below ambient temperature AC: +10 °C to -15 °C				
	Power input	DC: 47 W AC: 75 W				
	Current consumption at 12 V	3.9 Ah/h at +20 °C ambient temperature, at +5 °C interior temperature				
	Energy class	A+				
	Insulation	PU-foam				
	System	Thermoelectrics + 230-V compressor, electronic thermostat in compressor mode				
	Refrigerant	R134a: 38 g, CO ₂ equivalent: 0.054 t, Global warming potential (GWP): 1430				
	Quality Features	Powerful compressor powered by 230 V AC for cooling or freezing; additional thermoelectric unit for use with 12 V battery for cooling only, Extra-strong insulation with all-round rubber seal, 38 l capacity has space for 2 l bottles, Portable cooler with high efficiency, Digital temperature display, Continuous temperature adjustment				
	Material	Cabinet: coated sheet steel, Top and base: plastic				
	Colour	Black				
	Weight	22 kg				
	Test marks	TÜV/GS, E-certified (Automotive EMC Directive)				
Product	Dometic CK 40D Hybrid	<table border="1"> <thead> <tr> <th>Ref. No.</th> <th>Ref. No. UK</th> </tr> </thead> <tbody> <tr> <td>9600000482</td> <td>9600000572</td> </tr> </tbody> </table>	Ref. No.	Ref. No. UK	9600000482	9600000572
Ref. No.	Ref. No. UK					
9600000482	9600000572					




Lightweight, low-cost, versatile – these are the hallmarks of thermoelectric refrigeration. The wear-free technology is great for cooling or heating of small to medium-sized spaces. The Dometic range gives you a choice of three product families. Our practical “board bars” can be fastened to the seat with the safety belt to keep chilled drinks or warm snacks within convenient

reach during the journey. Our versatile CoolFun boxes are great for work and spare time use. The high-tech coolers in the TCX series satisfy highest demands, featuring an intelligent power-save circuit, individually adjustable temperature, and an active battery protection system that prevents excessive discharging of the vehicle battery.

DOMETIC BORDBAR TF 14

4.08




Thermoelectric car cooler, 14 l

	Storage volume	approx. 14 l		
	Connections	12 V DC		
	Temperature range	Cooling up to 25 °C below ambient temperature		
	Consumption	36 W at 12 V DC		
	Insulation	PU foam all around		
	System	Thermoelectric (Peltier system)		
	Quality Features	<ul style="list-style-type: none"> Stylish design in silky champagne colour Reinforced insulation for cooling up to 25 °C below ambient temperature Lightweight, compact and easy to transport Easy to fasten with safety belt Vertical space for standing 2 l bottles Powered from cigarette lighter socket 		
	Material	Textile cover in high-quality Oxford nylon, sides in hard-wearing, rubber-coated nylon		
	Colour	Champagne/black		
	Weight	4.6 kg		
	Test marks	TÜV/GS, E-certified (Automotive EMC Directive)		
Product	Dometic BordBar TF 14	<table border="1"> <thead> <tr> <th>Ref. No.</th> </tr> </thead> <tbody> <tr> <td>9600000499</td> </tr> </tbody> </table>	Ref. No.	9600000499
Ref. No.				
9600000499				

DOMETIC BORDBAR TB 08 / TB 15

4.08



Thermoelectric car cooler, 8 l and 15 l

	TB 08	TB 15	
  	Storage volume	approx. 8 l	approx. 15 l
	Connections	12 V DC	
	Temperature range	Cooling max. 20 °C below ambient temperature Heating up to +65 °C	
	Current consumption at 12 V	32 W	40 W
	Insulation	ISOFOAM	PU foam all around
	Quality Features	Fits 0.33 l cans and 0.5 l bottles	Active Battery Security, Fits 1.5 and 2 l bottles
	Material	PP	ABS
	Colour	Dark grey / pale grey	
	Weight	3.2 kg	5.2 kg
	Test marks	TÜV/GS, E-certified (Automotive EMC Directive)	
Product	Ref. No.		
Dometic BordBar TB 08	9600000488		
Dometic BordBar TB 15	9600000489		
/ Optional extras			
Mains adapter EPS 817, 230 V AC > 12 V DC	9600000439		
Voltage monitor CoolPower M 50U, 12 V, 5 A (only for TB 08)	9600000446		

DOMETIC BORDBAR AS 25

4.08



Thermoelectric car cooler, 20 l

 	Storage volume	approx. 20 l
	Connections	12 V DC / 230 V AC
	Temperature range	Cooling 18 °C below ambient temperature
	Power input	35 W
	Consumption at 12 V at 230 V	36 W 40 W
	Energy class	A++
	Insulation	PU foam all around
	System	Thermoelectric (Peltier system)
	Quality Features	Fits 2 litre bottles standing upright, Two zip-closure pockets, one net pocket, one cable compartment
	Colour	Dark grey / pale grey
Weight	4.3 kg	
Test marks	TÜV/GS, E-certified (Automotive EMC Directive)	
Product	Ref. No.	
Dometic BordBar AS 25	9600000459	

DOMETIC COOLFUN SC 26T

4.08



Portable thermoelectric cooler, 25 l

 	Storage volume	approx. 25 l
	Connections	12 / 24 V DC
	Temperature range	Cooling max. 18 °C below ambient temperature
	Current consumption at 12 V	47 W
	Insulation	Neopor
	Quality Features	Versatile carrying handle serves to support or lock the lid, USB port for charging mobile devices, 25 l capacity has room for 2 l bottles, Cooling up to 18 °C below ambient temperature, 12/24 V DC
	Material	PP
	Colour	Dark grey / pale grey
	Weight	3.7 kg
	Test marks	TÜV/GS, E-certified (Automotive EMC Directive)
Product	Ref. No.	
Dometic CoolFun SC 26T	9600000485	
/ Optional extras		
Mains adapter EPS 817, 230 V AC > 12 V DC	9600000439	

DOMETIC COOLFUN SC 30

4.08


Portable thermoelectric cooler 29 l

 	Storage volume	approx. 29 l
	Connections	12 V DC / 230 V AC
	Temperature range	Cooling max. 18 °C below ambient temperature, Heating up to +65 °C
	Current consumption at 12 V at 230 V	47 W 55 W
	Energy class	A++
	Insulation	Neopor
	Quality Features	Versatile carrying handle serves to support or lock the lid, USB port for charging mobile devices, 29 l capacity has room for 2 l bottles, Cooling up to 18 °C below ambient temperature, Heats up to +65 °C, Ready for use with 12 V DC or 230 V AC
	Material	PP
	Colour	Dark grey / pale grey
	Weight	4.0 kg
Test marks	TÜV/GS, E-certified (Automotive EMC Directive)	
Product	Ref. No.	
Dometic CoolFun SC 30	9600000486	
/ Optional extras		
Mains adapter EPS 817, 230 V AC > 12 V DC	9600000439	

DOMETIC COOLFUN SC 30B

4.08


Portable thermoelectric cooler with biocomposite material, 29 l

	Storage volume	approx. 29 l
	Connections	12 V DC / 230 V AC
	Temperature range	Cooling max. 18 °C below ambient temperature, Heating up to +65 °C
	Current consumption at 12 V	47 W
	at 230 V	55 W
	Energy class	A++
	Insulation	Neopor
	Quality Features	Fully recyclable biocomposite material minimizes waste, 26 % reduction of the CO ₂ footprint compared to conventional polypropylene, Improved durability saves fossil fuels without compromising on product performance, Versatile carrying handle serves to support or lock the lid, USB port for charging mobile devices
	Material	PP / Trifilon BioLite
	Colour	Beige / pale grey
	Weight	4.3 kg
	Test marks	TÜV/GS, E-certified (Automotive EMC Directive)
	Product	Ref. No.
	Dometic CoolFun SC 30B	9600024482
/ Optional extras		
Mains adapter EPS 817, 230 V AC > 12 V DC	9600000439	

DOMETIC TROPICOOOL TCX 14

4.36


Portable thermoelectric cooler, 14 l

	Storage volume	approx. 14 l
	Connections	12/24 V DC / 230 V AC
	Temperature range	Cooling max. 27 °C below ambient temperature, Heating up to +50 to +65 °C
	Consumption at 12 V DC	46 W
	at 24 V DC	50 W
	at 230 V AC	64 W
	Energy class	A++
	Insulation	PU foam all around
	Material	Injection moulded parts
	Quality Features	Convenient 12 or 24 V DC and 230 V AC cooler, active battery protection prevents deep discharge of the vehicle battery, very efficient TC special electronics with intelligent power-save circuit, reverse polarity protection for hassle-free electrical connections, priority circuit for mains operation, wear-resistant fan for dynamic interior ventilation
	Colour	Dark grey / pale grey
	Weight	5.0
	Test marks	TÜV/GS, E-certified (Automotive EMC Directive)
	Product	Ref. No.
Dometic TropiCool TCX 14	9600013319	9600013929
/ Optional extras		
Universal fixing kit	9105303709	
Mains adapter EPS 817, 230 V AC > 12 V DC	9600000439	
Voltage monitor CoolPower M 50U	9600000446	

DOMETIC COOLFUN SC 38

4.08


Thermoelectric cooler with wheels and telescopic handle, 37 l

	Storage volume	approx. 37 l
	Connections	12 V DC / 230 V AC
	Temperature range	Cooling max. 18 °C below ambient temperature, Heating up to +65 °C
	Current consumption at 12 V	47 W
	at 230 V	55 W
	Energy class	A++
	Insulation	PU
	Material	PP
	Quality Features	Versatile carrying handle serves to support or lock the lid, USB port for charging mobile devices, Wheels and telescopic handle, Split lid and removable partition
	Colour	Dark grey / pale grey
	Weight	5.3 kg
	Test marks	TÜV/GS, E-certified (Automotive EMC Directive)
	Product	Ref. No.
	Dometic CoolFun SC 38	9600000487

DOMETIC TROPICOOOL TCX 21

4.36



Portable thermoelectric cooler, 20 l

	Storage volume	approx. 20 l
	Connections	12/24 V DC / 230 V AC
	Temperature range	Cooling max. 27 °C below ambient temperature, Heating up to +50 to +65 °C
	Consumption at 12 V DC	46 W
	at 24 V DC	50 W
	at 230 V AC	64 W
	Energy class	A++
	Insulation	PU foam all around
	Material	Injection moulded parts
	Quality Features	Convenient 12 or 24 V DC and 230 V AC cooler, active battery protection prevents deep discharge of the vehicle battery, very efficient TC special electronics with intelligent power-save circuit, reverse polarity protection for hassle-free electrical connections, priority circuit for mains operation, wear-resistant fan for dynamic interior ventilation
	Colour	Dark grey / pale grey
	Weight	6.0 kg
	Test marks	TÜV/GS, E-certified (Automotive EMC Directive)
	Product	Ref. No.
Dometic TropiCool TCX 21	9600013320	9600013930
/ Optional extras		
Universal fixing kit	9105303709	
Mains adapter EPS 817, 230 V AC > 12 V DC	9600000439	
Voltage monitor CoolPower M 50U	9600000446	


DOMETIC TROPICOOOL TCX 35

4.36

Portable thermoelectric cooler, 33 l



Storage volume	approx. 33 l	
Connections	12/24 V DC / 230 V AC	
Temperature range	Cooling max. 27 °C below ambient temperature, Heating up to +50 to +65 °C	
Consumption at 12 V DC	46 W	
Consumption at 24 V DC	50 W	
Consumption at 230 V AC	64 W	
Energy class	A++	
Insulation	PU foam all around	
Material	Injection moulded parts	
Quality Features	Convenient 12 or 24 V DC and 230 V AC cooler, active battery protection prevents deep discharge of the vehicle battery, very efficient TC special electronics with intelligent power-save circuit, reverse polarity protection for hassle-free electrical connections, priority circuit for mains operation, wear-resistant fan for dynamic interior ventilation	
Colour	Dark grey / pale grey	
Weight	10.0 kg	
Test marks	TÜV/GS, E-certified (Automotive EMC Directive)	
Product	Ref. No.	Ref. No. UK
Dometic TropiCool TCX 14	9600013321	9600013931
/ Optional extras		
Universal fixing kit	9105303709	
Mains adapter EPS 817, 230 V AC > 12 V DC	9600000439	
Voltage monitor CoolPower M 50U	9600000446	

ACCESSORY FOR THERMOELECTRIC COOLERS**DOMETIC COOLPOWER EPS 817**

Mains adapter, from 230 V to 12 V

- Connects 12 V thermoelectric cooling boxes to the 230 V mains socket

Ref. No. 9600000439

**DOMETIC COOLPOWER M 50U**

Battery monitor for universal 12 V applications

- Protects the vehicle battery from excessive discharging
- Switches the cooling box off at low battery voltage and on again at normal voltage
- Ideal for older 12 V thermoelectric cooling devices with cigarette lighter socket as output

Ref. No. 9600000446

**DOMETIC TROPICOOOL TCX-FK**

Vehicle fixing kit for TC and TCX 14 – 35

- For secure use of cooler while on the move
- For safe fastening of cooler
- Heavy duty straps

Ref. No. 9105303709





12 volts DC, 230 volts AC or gas – CombiCool ACX absorption coolers from Dometic give you maximum freedom in terms of energy supply. They can be used in the vehicle, on a mains socket or in remote locations where electricity is unavailable. The ACX 40G is even more versatile, it works on a standard gas cartridge.

All three ACX models provide cooling up to 30 °C below the ambient temperature. Based on Dometic’s well proven absorption cooling technology, they are absolutely noiseless in operation. Another hallmark of the ACX family is the elegant aluminium housing with the distinctive lid.

DOMETIC COMBICOOL ACX 35

4.37



Portable absorption cooler, 31 l

 	Storage volume	approx. 31 l
	Connections	12 V DC / 230 V AC, LPG
	Temperature range	Cooling max. 30 °C below ambient temperature
	Consumption at 12 V DC	75 W
	at 230 V AC	75 W
	Gas	50 mbar: 12.3 g/h 30 mbar: 11.7 g/h
	Insulation	PU foam all around
	Material	Aluminium
	Quality Features	<ul style="list-style-type: none"> Absolutely silent operation means no disturbance Sturdy housing and attractive design Ice cube tray included Elegant aluminum housing Three-stage flame regulation in gas mode
	Colour	Aluminium finish / black
Weight	14 kg	
Test marks	Certified to European Gas Appliance Directive 90/396/EEC	
Product	Ref. No.	
Dometic CombiCool ACX 35 (50 mbar) D, CH, A	9105204279	
Dometic CombiCool ACX 35 (30 mbar) D, CH, A with hose, only permitted for use on a gas socket (coupling)	9105204290	
Dometic CombiCool ACX 35 (30 mbar) DK, FI, N, S	9105204280	
Dometic CombiCool ACX 35 (28 – 30 / 37 mbar) UK	9105204281	
Dometic CombiCool ACX 35 (28 – 30 / 37 mbar) F, I, E, NL	9105204282	

DOMETIC COMBICOOL ACX 40

4.37



Portable absorption cooler, 40 l

 	Storage volume	approx. 40 l
	Connections	12 V DC / 230 V AC, LPG
	Temperature range	Cooling max. 30 °C below ambient temperature
	Consumption at 12 V DC	85 W
	at 230 V AC	85 W
	Gas	50 mbar: 12.3 g/h 30 mbar: 11.7 g/h
	Insulation	PU foam all around
	Material	Aluminium
	Quality Features	<ul style="list-style-type: none"> Absolutely silent operation means no disturbance Sturdy housing and attractive design Ice cube tray included Elegant aluminum housing Three-stage flame regulation in gas mode
	Colour	Aluminium finish / black
Weight	15 kg	
Test marks	Certified to European Gas Appliance Directive 90/396/EEC	
Product	Ref. No.	
Dometic CombiCool ACX 40 (50 mbar) D, CH, A	9105204284	
Dometic CombiCool ACX 40 (30 mbar) D, CH, A with hose, only permitted for use on a gas socket (coupling)	9105204288	
Dometic CombiCool ACX 40 (30 mbar) DK, FI, N, S	9105204285	
Dometic CombiCool ACX 40 (28 – 30 / 37 mbar) UK	9105204286	
Dometic CombiCool ACX 40 (28 – 30 / 37 mbar) F, I, E, NL	9105204287	

DOMETIC COMBICOOL ACX 40G

4.37

Portable absorption cooler, 40 l (gas cartridge use)

 	Storage volume	approx. 40 l
	Connections	12 V DC / 230 V AC, Gas cartridge
	Temperature range	Cooling max. 30 °C below ambient temperature
	Consumption at 12 V DC	85 W
	at 230 V AC	85 W
	Gas	9.8 g/h
	Insulation	PU foam all around
	Material	Aluminium
	Quality Features	<ul style="list-style-type: none"> Absolutely silent operation means no disturbance Sturdy housing and attractive design Ice cube tray included Elegant aluminum housing Three-stage flame regulation in gas mode
	Colour	Aluminium finish / black
Weight	15 kg	
Test marks	Certified to European Gas Appliance Directive 90/396/EEC	
Product	Ref. No.	
Dometic CombiCool ACX 40G	9105204291	
Dometic CombiCool ACX 40G, UK	9105204289	



ICEBOXES IN HEAVY DUTY QUALITY

Dometic iceboxes feature an extremely effective insulation system. Fitted with ice packs or ice cubes, they can keep groceries, fish, bait and wild game fresh for several days. The new facelift models of the popular series are even cooler. Practical accessories like seat cushions, fishing rod holders and bottle openers make them

indispensable companions for fishermen, hunters and other nature lovers. The modular storage system, consisting of wire baskets and dividers, organises the content. Available for all new Cool-Ice models (43 to 111 litres).

DOMETIC COOL-ICE WCI 13 / 22 / 33

Insulation box

	WCI 13	WCI 22	WCI 33
Storage volume (approx.)	13 l	22 l	33 l
Dimensions (W x H x D)	388 x 305 x 245 mm	388 x 313 x 365 mm	400 x 440 x 360 mm
Weight (approx.)	2.8 kg	4.2 kg	5.7 kg
Material	Rotomoulded PE		
	Product		Ref. No.
	Dometic Cool-Ice WCI 13		9600000500
	Dometic Cool-Ice WCI 22		9600000501
	Dometic Cool-Ice WCI 22, Nato green		9600019218
	Dometic Cool-Ice WCI 33		9600000502

DOMETIC COOL-ICE CI 42 / 55 / 70

Insulation box

	CI 42	CI 55	CI 70
Storage volume (approx.)	43 l	56 l	71 l
Dimensions (W x H x D)	640 x 335 x 418 mm	570 x 432 x 515 mm	690 x 432 x 515 mm
Weight (approx.)	8.7 kg	10.6 kg	11.8 kg
Material	Rotomoulded PE		
	Product		Ref. No.
	Dometic Cool-Ice CI 42		9600000541
	Dometic Cool-Ice CI 42, Nato green		9600019219
	Dometic Cool-Ice CI 55		9600000542
	Dometic Cool-Ice CI 70		9600000543

DOMETIC COOL-ICE CI 85 / 85W / 110

4.08

Insulation box

	CI 85	CI 85W	CI 110
			
			
Storage volume (approx.)	87 l	86 l	111 l
Dimensions (W x H x D)	840 x 432 x 525 mm	840 x 432 x 525 mm	1055 x 442 x 535 mm
Weight (approx.)	14 kg	14.6 kg	18.1 kg
Material	Rotomoulded PE		
	Product	Ref. No.	
	Dometic Cool-Ice CI 85	960000544	
	Dometic Cool-Ice CI 85W	960000545	
	Dometic Cool-Ice CI 110	960000546	

DOMETIC COOL-ICE ACCESSORY

Dometic Cool-Ice CI series – Optional extras

	CI 42	CI 55	CI 70	CI 85	CI 85W	CI 110
 Seat Cushion		9108400893	9108400894	9108400895	9108400895	9108400896
 Divider	9108400897	9108400898	9108400898	9108400898	9108400898	9108400898
 Basket Small	9108400899	9108400900	9108400900	9108400900	9108400900	9108400900
 Beverage Holder & Bracket	9108400901	9108400901	9108400901	9108400901	9108400901	9108400901
 Beverage Holder	9108400902	9108400902	9108400902	9108400902	9108400902	9108400902
 Rod Holder	9108400903	9108400903	9108400903	9108400903	9108400903	9108400903
 Bottle Opener	9108400904	9108400904	9108400904	9108400904	9108400904	9108400904
 Fixing Kit	9108400905	9108400905	9108400905	9108400905	9108400905	9108400905